





Long Tail Image Generation Through Feature Space Augmentation and Iterated Learning

Rafael Elberg^{1,2,3}, Denis Parra^{1,2,3}, Mircea Petrache^{1,2}
{rafael.elberg, denis.parra, mpetrache}@uc.cl
[1] Pontificia Universidad Católica de Chile, [2] CENIA, [3] iHealth




Introduction


- ◆ Specific domains are naturally **Long Tailed** (Medical image domain).
- ◆ SOTA image augmentation methods suffer with long tailed data, reduced sample quality and interference between features.
- ◆ Compositional Learning, IL and SE.
- ♦ We propose creating a sparse, disentangled latent space from a pretrained Diffusion Model to fuse important features from tail examples with unimportant features from head examples.

Background

- ◆ Simplicial Embbeddings and Iterated Learning create Compositional Mappings[1].
- MIMIC-CXR-LT[2] is a Long Tailed Dataset of Chest X Ray images and anomaly labels.
- ◆ By separating samples into their components, we can create new tail class data points by fusing class generic features from head samples and class specific features from tail samples[3].



Examples + No finding mage No finding mage New support devices image New support devices image Atelectasis Near Neighbor Aorta Image New Tortuous Aorta Image



Experiments

- ◆ Classification on a reduced set of MIMIC-CXR-LT. We train a DenseNet121 on the original training set, and a set augmented with: RoentGen[4] at 75 inference steps, SMOTE[5], and our method.
- ◆ We use RoentGEN as our Stable Diffusion Model, testing 0, 1 and 5 inference steps.
- ◆ We also evaluate image generation quality (FID).

Results

Model	Generation Avg Tail FID	Classification	
		Head mAP	Tail mAP
Baseline	_	0.618	0.155
SMOTE	171.864	0.578	0.151
RoentGEN @ 75	138.963	0.618	0.152
Ours @ 0	191.873	0.607	0.152
Ours @ 1	191.646	0.595	0.143
Ours @ 5	130.110	0.595	0.144

Conclusions and Future Work

- ◆ We obtain competitive results in image generation quality using only 5 inference steps. Counter intuitively, more inference steps reduce data augmentation effectiveness. Our reasoning suggests this is due to the diffusion process not respecting existing labels.
- We plan to experiment with larger datasets and a broader range of domains, and to evaluate on compositional generalization specific tasks. We also want to include the mask generation in the learning process, and evaluate different ways to assign labels..

References

[1] Ren, Y., Lavoie, S., Galkin, M., Sutherland, D. J., & Courville, A. (2023, October 28). *Improving compositional generalization using iterated learning and simplicial embeddings*. arXiv.org. https://arxiv.org/abs/2310.18777

[2] Holste, G., Wang, S., Jaiswal, A., Yang, Y., Lin, M., Peng, Y., & Wang, A. (2023). CXR-LT: Multi-Label Long-Tailed Classification on Chest X-Rays (version 1.1.0). PhysioNet. https://doi.org/10.13026/c4tr-kr83.

[3] Chu, P., Bian, X., Liu, S., & Ling, H. (2020, August 9). Feature space augmentation for Long-Tailed data. arXiv.org. https://arxiv.org/abs/2008.03673
[4] Chawla, N. V., Bowyer, K. W., Hall, L. O., & Kegelmeyer, W. P. (2002). SMOTE: Synthetic Minority Over-sampling technique. Journal of Artificial

Intelligence Research/□the □Journal of Artificial Intelligence Research, 16, 321–357. https://doi.org/10.1613/jair.953
[5] Goldberger, A., Amaral, L., Glass, L., Hausdorff, J., Ivanov, P. C., Mark, R., ... & Stanley, H. E. (2000). PhysioBank, PhysioToolkit, and PhysioNet:

[5] Goldberger, A., Amaral, L., Glass, L., Hausdorff, J., Ivanov, P. C., Mark, R., ... & Stanley, H. E. (2000). PhysioBank, PhysioToolkit, and PhysioNo Components of a new research resource for complex physiologic signals. Circulation [Online]. 101 (23), pp. e215–e220.